

LOGIX SEMI-AUTOMATIC L-SEALERS



AP-1622A



AP-2028A



AP-3040A

LOGIX PREMIUM models are geared to moderate volume users in production environments. With a more powerful magnet system and faster, more efficient arm controls, these units offer the best quality ROI in the marketplace.

Features

- Power belted discharge conveyor
- Dual magnet clamping
- Pin perforation hold punch
- Variable dwell/seal time
- Variable conveyor time
- Seal head return cylinder
- Locking casters
- Linear bearings allow sealing platform movement for perfect alignment

| Item | Model | Power | | | Weight | Dim. (L x W x H) | Sealing Size |
|--------|----------|---------|-------|-----|--------|---------------------|--------------|
| | | Voltage | Phase | Amp | | | |
| 186050 | AP-1622A | 220V | 1 | 15 | 320 lb | 63 x 31 x 39" | 16 x 22" |
| 186052 | AP-2028A | 220V | 1 | 15 | 330 lb | 75 x 34 x 39" | 20 x 28" |
| 186053 | AP-3040A | 220V | 1 | 15 | 620 lb | 98 x 44 x 39" | 30 x 40" |

LOGIX SHRINK TUNNELS



AP-221044

Our LOGIX line of tunnels are suitable for most standard applications and come in a variety of sizes to couple with your choice of sealer and complete the shrink wrap process. Strong seals, consistent film shrinkage and excellent package appearance are guaranteed.

| Item | Model | Power | | | Weight | Machine Dim. (L x W x H) | Chamber Dim. (L x W x H) |
|--------|-----------|---------|-------|-----|--------|-----------------------------|-----------------------------|
| | | Voltage | Phase | Amp | | | |
| 186330 | AP-180828 | 220V | 3 | 25 | 455 lb | 42 x 28 x 60" | 28 x 18 x 8" |
| 186049 | AP-221044 | 220V | 3 | 30 | 710 lb | 61 x 31 x 62" | 44 x 22 x 10" |
| 186042 | AP-221248 | 220V | 3 | 30 | 750 lb | 66 x 31 x 64" | 48 x 22 x 12" |
| 186043 | AP-301048 | 220V | 3 | 25 | 820 lb | 66 x 44 x 61" | 48 x 30 x 10" |